

TS10

10' FLEX-WING



Fits Through Gates as Narrow as 8'



Average Mowing Time of 4 MPH



Walterscheid Ez-Loc Collar Makes Hookup Easy



Smooth, Quiet Operation



Replaceable Skid Shoes for Simple Maintenance



Heavy-Duty Turn Buckles for Fewer Breakdowns and Less Stress



TS10

SPECIFICATIONS

Specifications	TS10
Cutting Width:	120"
Transport Width:	93"
Transport Height:	68"
Overall Length:	162"
Cutting Height:	1" - 15" (Dependent on Tire Size)
Height Adjustment:	3 1/2" x 8" Hydraulic Cylinder
Hitch:	Pull Type, Parallel Clevis
Blade Carrier:	Infinity - Steel
Blades:	1/2" x 3" High Lift
Tractor HP Required:	25 PTO
Cutting Capacity:	2"
Driveline ASABE:	CAT 4 CV (Main) / CAT 3 SC (Wing)
Deck Thickness:	12 Ga
Side Skirt:	1/4" x 10"
Tires & Wheels:	4 or 6, 20" Laminated, Aircraft or Foam Filled Rhino Trax
Wing Flex (Degrees):	90° Up, 22° Down
Safety Deflectors:	Deflectors or Chains
Tongue Weight:	720 lbs
Weight (Approx):	2,190 lbs