

RhinoAg: **Finish Mowers**

▶ **FA SERIES**



Available in 60", 72", and 84" cutting widths



Easy access to conventional height adjustments



Tapered, sloped discharge area for even distribution of cut material across the deck



Over-the-deck ale design provides outstanding structural integrity



Three blade design and 1" overlap to eliminate streaks and improve cut-quality



Durable ABS safety shield with easy access to lubrication points



Built in baffles for increased air and material flow through cutting chamber



Ideally suited for homeowners, golf courses, parks, schools, recreation areas

RHINOAG

FA SERIES

Specifications	FA513	FA613	FA713
Mowing Width:	5' (60")	6' (72")	7' (84")
Overall Width:	63"	75"	87"
Number of Blades:	3		
Cutting Height:	3/4" - 4 1/4"		1-1/2" - 4 1/2"
Height Adjustment:	Bushing		
Hitch:	CAT 1		
Blades:	6mm x 60mm		
Blade Overlap:	1"		
PTO HP Required:	16 - 40	22 - 50	30 - 60
Gearbox Ratio:	1:2.8		
Blade Tip Speed:	14,070 FPM	14,183 FPM	15,257 FPM
Cutting Capacity (Max.):	Grass		
Driveline Size:	CAT 3 ASAE		
Drive Belt Section:	"B"		
Number of Drive Belts:	2		
Deck Thickness:	4mm (.157")	5mm (.197")	
Tires & Wheels:	Solid		
Anti-Scalp Roller:	Standard		
Discharge:	Rear		
Weight (Approx):	432 lbs	472 lbs	816 lbs

**1 YEAR
LTD
WARRANTY**

FULL MACHINE

1-YEAR WARRANTY
Industry-leading toughness,
industry-leading warranty



DURABLE SAFETY SHIELD
provides easy access to lube points



BUILT-IN BAFFLES
improve air and material through the deck